

	1	2	3	4	5	6	7	8	9	10	11	12	13	14	
A															A
B															B
C															C
D															D
E															E
F															F
G															G
H															H
I															I
J															J

Dämpfung/Attenuation @ 20 °C in dB/100 m	100 dB Koaxial-Antennenkabel 2 x geschirmtes Kabel für HDTV aus recyceltem Kupfer	100 dB Coaxial Antenna Cable 2 x copper/steel mix cable for HDTV
- 100 MHz-5.7 dB - 200 MHz-8.8 dB - 300 MHz-9.0 dB - 500 MHz-12.6dB - 800 MHz-18.4 dB - 1000 MHz-20.8 dB - 1350 MHz-24.9 dB - 1750 MHz-28.5 dB - 2050 MHz-32.2 dB	- (1) Innenleiter 1,1 mm CU (CCC) - (2) Aussendurchmesser 6,9 mm - Schirmungsmaß 100 dB - Schirmung zweifach (3) 1. Schirm: AL-Folie (4) 2. Geflecht: 64 Adern - Impedanz 75 Ω - Isolation PVC; grau - (5) Dielektrikum 4.57 mm FPE - Länge 100 m - Verpackungsart Papp-Spule - Gewicht 4.179 kg RoHS-konform	- (1) Inner conductor 1.1 mm CU (CCC) - (2) Outer diameter 6.9 mm - Screening immunity 100 dB - Shielding double (3) 1st - screen: AL-foil (4) 2nd - braid: 64 cores - Impedance 75 Ω - Insulation PVC; gray - (5) Dielectric 4.57 mm FPE - Length 100 m - Packaging type Paper spool - Weight 4.179 kg RoHS compliant

Änderungen		Datum	Name	Bezeichnung	Blatt
Datum	Name	gez.: 12.11.2014	tf	KOAXKABEL 2-100 CU, 100m	von
		gepr.: 12.11.2014	tf		
		Norm:		Zeichnungs-Nr.: 27558	
Änderungen vorbehalten / Subject to change					