



Anschlussdiagramm / Wiring diagram

TYPE C PCB			TYPE C PCB	
A4 B4	Red VCC	A4 B4 A9 B9	A4 B4	A9 B9
A6 B6			A6 B6	
A7 B7	White D+	A7 B7	A7 B7	A7 B7
A1 B1	Green D-		A1 B1	
A12 B12	Black VCC	A12 B12	A12 B12	A12 B12
A5 CC	0.254 CU GND		A5 CC	

USB-C™ Lade- und Synchronisationskabel

- USB 2.0 Kabel zum Synchronisieren und Laden
- USB-C™-Stecker beidseitig verwendbar
- Anschlüsse: 2x USB-C™-Stecker
- Kontakte: vernickelt
- max. Stromstärke: 3 A
- max. Datenübertragungsrate: 480 Mbit/s
- Kabeltyp: Rundkabel
- Innenleiter: 28 AWG + 20 AWG
- Material: 45P PVC
- Konformität: RoHS

USB-C™ charging and sync cable

- USB 2.0 cable for synchronising and charging
- USB-C™ connector can be used on both sides
- Connectors: 2x USB-C™ plug
- Contacts: nickel-plated
- max. Amperage: 3 A
- max. Data rate: 480 Mbit/s
- Cable type: round cable
- Inner conductors: 28 AWG + 20 AWG
- Material: 45P PVC
- Conformity: RoHS

Änderungen				Datum	Name	Bezeichnung	Blatt
Datum	Name	gez.:	11.01.2021	RS	DAT USB-C/C v2.0		1
		gepr.:	11.01.2021	aw			
		Norm:					
Änderungen vorbehalten / Subject to change						Zeichnungs-Nr.: 51243, 51244	von 1